



Steel quality

Steel: s355 + hot-dip galvanized acc. EN ISO 1461

Threaded rods: 8.8 FZV

U-bolts: s355 FZV

Performance

Max vertical load per arm: 62,5kg

Max horizontal load per arm incl safety factor: 2,25kN

Max wind load area per arm incl form factor (C x A): 0,75m<sup>2</sup>

Max installation height: 70meter

Terrain classification: TC1

Reference wind speed: 27m/s

M10 nut tightening torque: 30Nm

M10 2nd nut tightening torque: 47Nm

Installation and maintenance guides are available on our website [www.telecomsteel.com](http://www.telecomsteel.com)

Basis for structural design is according to EN 1990:2007 and Danish National Annex DS/EN 1990/NA.

Manufacturing of the structure is carried out in accordance with Execution Class EXC2 as per EN 1090-1+A1:2012 and EN 1090-2:2018.

Governing environmental loading is assessed as wind load, and actions on structures are determined according to EN 1991-1-4 and Danish National Annex DS/EN 1991-1-4/NA. CE marking is performed in accordance with the Construction Products Regulation (CPR).



Designed by AndersPedersen	Checked by	Approved by	Date	Date 16-12-2025
		Extra SBS bracket 1080mm		
		50075	Revision D	Sheet 1 / 1